



Broj artikla		Ukupna debljina (mm)	Zahtevani minimalni prečnik remenice	Osnovna snaga remena (N/mm širine)	Radno istezanje (%)	Maksimalna nosiva snaga remena po obimu (N/mm po širini remena)	Opterećenje osovine kod 1% istezanja (N/mm po širini remena)	Istezanje pri postavljanju (%)	Težina (kg/m ²)	Dozvoljena radna temperatura (°C)	Proizvodna širina (mm)	Dužina "z" spoja (mm)	Klinasti spoj, brušeni	Pogonski remen	Tangencijalni remen	Vajličani pogonski remen	Vretenasti remen- tekstilna industrija	Mašinski remen	Noseći remen
A tip																			
UU 15 A-17 FSTR / FSTR	zelena	995473	1,7	30	15	0,5	15	0,3-0,8	1,9	-20/+70	1000	110		•		•			
GG 25 A- 20	plava	822042	2,0	40	25	0,5	32	0,3-0,8	2,25	-20/+70	1000	110		•	•				
GG 25 A- 25	plava	822045	2,5	60	25	0,5	32	0,3-0,8	2,7	-20/+70	1000	110		•	•				
GG 40 A- 32	plava	822046	3,2	90	40	0,5	50	0,3-0,8	3,45	-20/+70	1000	110		•	•				
E tip																			
GG 15 E- 18	zelena	822053	1,8	25	15	2,0	15	1,0-2,0	2,0	-20/+70	1000	35 / 70		•	•				
UU 20 E- 16 FSTR /FSTR	zelena	822055	1,6	40	20	2,0	25	0,3-2,0	1,85	-20/+70	1000	70			•				
GG 20 E- 20	zelena	822052	2,0	30	20	2,0	20	1,0-2,0	2,3	-20/+70	1000	35 / 70		•	•	•			•
UU 30 E- 32 FSTR / FSTR	zelena	822105	3,2	40	20	2,0	25	0,3-2,0	3,55	-20/+70	1000	70		•	•	•			
GG 25 E- 25	zelena	822074	2,5	60	25	2,0	25	1,0-2,5	2,65	-20/+70	1000	35 / 70		•	•	•			•
GG 30 E- 32	zelena	822051	3,2	40	30	2,0	30	1,0-2,0	3,4	-20/+70	1000	70		•	•	•			
GG 30 E- 40 ***	zelena	822054	4,0	60	30	2,0	30	1,0-2,0	4,3	-20/+70	1000	70		•	•				
UT 8 E	zelena/bela	822060	0,7	15			8	0,3-2,0	0,6	-20/+70	1000	35					•	•	
UU 8 E	zelena	995451	1,5	15			8	0,3-1,5	1,7	-20/+70	1000	35						•	•
PU 8 E	zelena	995453	1,4	25			8	0,3-1,5	1,45	-20/+70	1000	35						•	•
GG 3 E	zelena	825558	1,5	20			3	0,3-2,0	1,5	-20/+70	1000	35						•	•
GG 8 E	zelena	822026	1,5	30			8	0,3-2,0	1,6	-20/+70	1000	35		•				•	•
TT 6 E	crna / siva	822103	1,0	15			6	0,3-2,0	1,0	-20/+70	1000	35						•	•
TT 10 E	zelena	822072	1,1	25			10	0,3-2,0	1,15	-20/+70	1000	35						•	•
TT 10 E- HC	crna	822096	1,0	15			10	0,3-2,0	1,0	-20/+70	1000	35						•	•
TT 15 E	siva	822070	1,8	25			15	0,3-2,0	1,5	-20/+70	500	35						•	•
TG 6 E	crna / zelena	822080	1,0	15			6	0,3-2,0	1,2	-20/+70	1000	35						•	•
TG 10 E	crna / zelena	822081	1,3	25			10	0,3-2,0	1,4	-20/+70	1000	35						•	•
UN 6 E	zelena/siva	822091	1,9	15			6	0,3-2,0	2,0	-20/+70	1000	35						•	•
GG 20 E- 30	zelena	855538	3,0	40	20	2,0	25	0,3-2,0	3,4	-20/+70	1000	35 / 70		•		•			•
GG 20 E- 40	zelena	855540	4,0	40	20	2,0	25	0,3-2,0	4,3	-20/+70	1000	70		•					•
GG 20 E- 55 ***	zelena	822050	5,5	50	20	2,0	25	0,3-2,0	6,0	-20/+70	1000	70		•					•
TG 30 E- 30	crna / siva	822058	3,0	60			30	1,0-2,0	3,2	-20/+70	500	35 / 70				•			
P tip																			
LL 6 P		800015	3,0	35	6	2,0	7,5	1,5-3,0	2,95	-20/+80	500		•	•					
LL 10 P ***		800016	3,1	40	10	2,0	12,5	1,5-3,0	3,1	-20/+80	500		•	•					
LL 14 P		800017	3,5	60	14	2,0	17,5	1,5-3,0	3,6	-20/+80	500		•	•					
LL 20 P		800018	4,4	90	20	2,0	25	1,5-3,0	4,2	-20/+80	500		•	•					
LL 28 P		800019	4,9	200	28	2,0	35	1,5-3,0	5,0	-20/+80	1000		•	•					
LL 40 P ***		800020	5,9	280	40	2,0	48	1,5-3,0	5,6	-20/+80	1000		•	•					
LT 6 P		800007	2,0	35	6	2,0	7,5	1,5-3,0	1,9	-20/+80	500		•	•					
LT 10 P ***		800008	2,2	40	10	2,0	12,5	1,5-3,0	2,5	-20/+80	500		•	•					
LT 14 P		800009	2,4	60	14	2,0	17,5	1,5-3,0	2,6	-20/+80	500		•	•					
LT 20 P ***		800010	2,8	90	20	2,0	25	1,5-3,0	2,9	-20/+80	500		•	•					
LT 28 P		800011	3,7	200	28	2,0	35	1,5-3,0	3,7	-20/+80	1000		•	•					
LT 40 P ***		800012	4,4	280	40	2,0	48	1,5-3,0	4,3	-20/+80	1000		•	•					
LT 54 P		800013	5,5	380	54	2,0	67,5	1,5-3,0	5,5	-20/+80	1000		•	•					
LT 65 P ***		998059	5,8	460	65	2,0	84,5	1,5-3,0	5,7	-20/+80	1000		•	•					
LT 80 P ***		800014	7,2	560	80	2,0	110	1,5-3,0	7,1	-20/+80	1000		•	•					
GG 10 P	zelena	855543	1,9	30	10	2,0	12,5	1,5-3,0	1,9	-20/+80	500		•	•	•				
GG 14 P	zelena	855544	2,1	50	14	2,0	17,5	1,5-3,0	2,1	-20/+80	500		•	•					
GG 20 P	zelena	855545	2,6	70	20	2,0	25	1,5-3,0	2,9	-20/+80	500		•	•	•	•			
GG 20 P- Tex	zelena	855548	2,9	70	20	2,0	25	1,5-3,0	3,2	-20/+80	500		•	•	•				
GG 28 P	zelena	855549	3,2	120	28	2,0	35	1,5-3,0	3,6	-20/+80	500		•	•	•				
GG 34 P	zelena	855550	3,4	140	34	2,0	42,5	1,5-3,0	3,9	-20/+80	500		•	•	•				
GG 34 P- Tex	zelena	855551	4,0	140	34	2,0	42,5	1,5-3,0	4,5	-20/+80	500		•	•	•				
GT 6 P	zelena / crna	850388	1,3	25	6	2,0	9	1,5-3,0	1,3	-20/+80	500		•	•					
GT 10 P	zelena / crna	850381	1,6	30	10	2,0	12,5	1,5-3,0	1,6	-20/+80	500		•	•					
GT 14 P	zelena / crna	850382	1,8	50	14	2,0	17,5	1,5-3,0	1,8	-20/+80	500		•	•					
GT 20 P	zelena / crna	850383	2,5	70	20	2,0	25	1,5-3,0	2,65	-20/+80	500		•	•					
GT 28 P ***	zelena / crna	850384	3,0	120	28	2,0	35	1,5-3,0	3,3	-20/+80	1000		•	•					
GT 40 P	crna	850049	3,65	280	40	2,0	48	1,5-3,0	4,0	-20/+80	1000		•	•					
GT 54 P ***	crna	850050	4,4	380	54	2,0	67,5	1,5-3,0	4,9	-20/+80	1000		•	•					
GT 80 P ***	crna	850051	6,0	560	80	2,0	110	1,5-3,0	6,4	-20/+80	1000		•	•					
TT 2 P	zelena	850028	0,6	20			2	0,6-3,0	0,5	-20/+80	500		•						•
TG 2 P	zelena / siva	850029	0,8	20			2	0,6-3,0	0,8	-20/+80	500		•						•
GG 2 P	siva	850030	1,2	20			2	0,6-3,0	1,3	-20/+80	500		•						•
TG 3 P	zelena / siva	850034	1,1	25			3	0,6-3,0	1,0	-20/+80	500		•						•
GG 3 P	siva	850035	1,4	25			3	0,6-3,0	1,45	-20/+80	500		•						•
TT / S 3 P	zelena	850032	0,65	15			3	0,6-3,0	0,5	-20/+80	500		•						•
UT 5 P	zelena	995381	0,75	15			5	0,6-3,0	0,5	-20/+80	500		•						•
TT 4 P	crna / zelena	850217	0,65	25			4	0,6-3,0	0,6	-20/+80	500		•						•
TG 4 P	zelena / siva	850039	1,0	25			4	0,6-3,0	1,05	-20/+80	500		•						•
GG 4 P	siva	850040	1,4	25			4	0,6-3,0	1,6	-20/+80	500		•						•
NN 4 P- HC	crna	850335	1,6	25			4	0,6-3,0	1,3	-20/+80	500		•						•
TU 6 P	crna / zelena	850209	1,05	30			6	0,6-3,0	1,05	-20/+80	500		•						•
UU 6 P	zelena	850211	1,3	30			6	0,6-3,0	1,3	-20/+80	500		•						•
GG 6 P	siva	850007	1,5	30			6	0,6-3,0	1,7	-20/+80	500		•						•